









Mulcher with reversible hydraulic feeder, ideal for pruning of vineyard, dessert grapes, chestnut-trees, olive trees, almond-trees, citrus fruits, walnuts, hazels, etc.

For tractors between 100 and 160 HP. Machine for demanding works, with need to deposit very thin remains in the area, avoiding possible plagues and helping to their elimination, for later processes.

It has a rotor of crenellated cleavers, crossing with fixed palate.

CARACTERISTICS

- Steel-plate chassis, thickness 10 mm.
- Rotor with system RHENDUEL of 550 Ø mm of diameter.
- Gearbox SERRAT.
- Oscillating bearings of double row of rollers.
- PTO 1.000 rpm.
- Double hydraulic feeder, system BRALAKC.
- Power of tractor between 100 - 160 HP.
- Triple feed chain.
- Model built under EC Normative.
- Safety indicators visible to personnel.

MODEL	 mm	 KW-HP			N° BELT TYPE							
						A mm	A in	B mm	B in	C mm	C in	
T-1600	1600	74 - 100 119 - 160	6 x 8	1720	4 XPC	1865	73"	1845	73"	1000	39"	1000
T-1800	1800	81 - 110 119 - 160	6 x 9	1858	4 XPC	2065	81"	1845	73"	1000	39"	1000
T-2000	2000	88 - 120 119 - 160	6 x 10	1993	4 XPC	2265	90"	1845	73"	1000	39"	1000
T-2300	2300	96 - 130 119 - 160	6 x 11	2193	4 XPC	2565	101"	1845	73"	1000	39"	1000